



YKS450-1000 安装尺寸表(10000V)  
YKS450-1000 MOUNTING DIMENSIONS TABLE (10000V)

机座号	极数	安装尺寸及公差																		外形尺寸(限值)			
		A		B		C		D		E		F		G		H		K		AC	AD	HD	L1
		基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差	基本尺寸	极限偏差				
450	4-8	800	±1.75	1120	±1.75	355	±4.0	110	±0.57	210	±0.57	28	0	100	-0.2	450	0	35	+0.62	1200	900	1900	2200
500	4	900	±2.1	1250	±2.1	475		120		+0.040		250		±0.65		40		0		109	-0.3	500	-1.0
	6-12						130	150	160		170		185		203		230		2680				
560	4	1000	±2.1	1400	±2.1	500	±4.2	150	+0.017	350	±0.70	50	0	138	-0.074	560	-1.5	42	0	1420	1000	2300	3100
	6-12							160						170				185		203	230	2680	
630	4	1120	±2.8	1600	±2.8	530	±4.2	170	+0.046	410	±0.77	56	0	147	-0.3	630	-1.5	48	0	1600	1100	2500	3400
	6-12							180						200				220		250	280	320	3700
710	4~16	1400	±2.8	1800	±2.8	530	±4.2	200	+0.046	350	±0.70	50	0	185	-0.3	710	-1.5	56	0	1840	1180	2700	3300
800	4~16	1600		2000				220						250		280		320		3700			
900	4~16	1800	±3.5	2240	±3.5	600	±4.2	250	+0.052	470	±0.77	63	-0.074	230	-0.3	900	-1.5	66	0	2680	1530	3250	3800
1000	4~16	2000		2500				280						320		3700							

注: 1.H560-1000 采用端盖式滑动轴承结构。  
2.当采用滑动轴承时,C 尺寸的极限偏差不包括轴向窜动量。